

Restrict Content Macro Parameters and Key

Relates To

THEME PRESS

Restrict Content Macro Parameters and Key

Prompt

Restrict Content macro key and configuration options.

Key Title

Key

Key

restrict-content

Reference

Parameter	Description	Value(s)	Example(s)
Space Key(s)	grants access to space viewers; when the Any Space box is unchecked, users must have the View permission for all spaces	<ul style="list-style-type: none">space key	<ul style="list-style-type: none">PRESS PINBOARDSPRESS, PINBOARDS
Any Space	toggles between granting access to viewers of all spaces or any space	<ul style="list-style-type: none">checkboxmark	
Page Title	grants access to users who can view the specified page	<ul style="list-style-type: none">page title	<ul style="list-style-type: none">Theme Press MacrosPRESS:Theme Press Macros
Authenticated Users	defines how to handle access for authenticated users; inherit current macro restrictions, hide content, show content	<ul style="list-style-type: none">inherithideshow	
Anonymous Users	defines how to handle access for anonymous users; inherit current macro restrictions, hide content, show content	<ul style="list-style-type: none">inherithideshow	
Client Type	grants access to a specific type of computer client	<ul style="list-style-type: none">alldesktopmobile	<ul style="list-style-type: none">all
Allow Users	grants access to a list of users	<ul style="list-style-type: none">usernames	<ul style="list-style-type: none">charles_dickens, emily_dickinson
Allow Groups	grants access to a list of groups	<ul style="list-style-type: none">user groups	<ul style="list-style-type: none">confluence-users, theme-press-users
Exclude Users	restricts access from a list of users	<ul style="list-style-type: none">usernames	<ul style="list-style-type: none">charles_atlas, robbie_lee
Exclude Groups	restricts access from a list of groups	<ul style="list-style-type: none">user groups	<ul style="list-style-type: none">space-editors, guests
Display in Paragraph*	toggles between showing restricted content inline with other content or within its own paragraph	<ul style="list-style-type: none">checkboxmark	

HTTP Header Fields	grants access to HTTP requests when the HTTP header field matches any of the specified name/value pairs	<ul style="list-style-type: none">• header-name=value	<p>Plain matches:</p> <ul style="list-style-type: none">• City=Seattle• City=Seattle;City=Portland <p>Regular expression matches[†]:</p> <ul style="list-style-type: none">• ipaddress=/128\.128\.200\.d+/ • ipaddress=/128\.128\.200\.d+/ ipaddress=/128\.128\.210\.d+/ • User-Agent=/. *Mac.* / <p>[†]Entire value must match. Use .* or .+ to match unknown characters, as in the Mac example.</p> <p>We recommend using https://regex101.com/ for testing expressions.</p>
Match All Header Fields	toggles between granting access when any or all HTTP header fields match	<ul style="list-style-type: none">• checkmark	
Consolation Prize HTML Element	targets an HTML element and allows restricted users to see that content; use the HTML Wrap macro and its Hide parameter to insert the consolation prize element		

* Removed in 2.0.

Info

Related

- [Restrict Content Macro](#)
- [Macro Reference](#)