Restrict Content Macro Parameters and Key

Relates To

THEME PRESS

Restrict Content Macro Parameters and Key

Prompt
Restrict Content macro key and configuration options.

Key Title
Key

Key
restrict-content

Reference

Parameter	Description	Value(s)	Example(s)
Space Key(s)	grants access to space viewers; when the **Any Space** box is unchecked, users must have the **View** permission for all spaces	• space key	• `PRESS PINBOARDS` • `PRESS,PINBOARDS`
Any Space	toggles between granting access to viewers of all spaces or any space	• checkmark	
Page Title	grants access to users who can view the specified page	• page title	• `Theme Press Macros` • `PRESS:Theme Press Macros`
Authenticated Users	defines how to handle access for authenticated users; inherit current macro restrictions, hide content, show content	• inherit • hide • show	
Anonymous Users	defines how to handle access for anonymous users; inherit current macro restrictions, hide content, show content	• inherit • hide • show	
Client Type	grants access to a specific type of computer client	• all • desktop • mobile	• `all`
Allow Users	grants access to a list of users	• usernames	• `charles_dickens,emily_dickinson`
Allow Groups	grants access to a list of groups	• user groups	• `confluence-users,theme-press-users`
Exclude Users	restricts access from a list of users	• usernames	• `charles_atlas,robbie_lee`
Exclude Groups	restricts access from a list of groups	• user groups	• `space-editors,guests`
Display in Paragraph*	toggles between showing restricted content inline with other content or within its own paragraph	• checkmark	

HTTP Header Fields	grants access to HTTP requests when the HTTP header field matches any of the specified name/value pairs	• header-name=value	`Plain matches:`
			• `City=Seattle`
			• `City=Seattle;City=Portland`
			
			`Regular expression matches†:`
			• `ipaddress=/128\.128\.200\.d+/`
			• `ipaddress=/128\.128\.200\.d+/;ipaddress=/128\.128\.210\.d+/`
			• `User-Agent=/.*Mac.*/`
			
			`†Entire value must match. Use .* or .+ to match unknown characters, as in the Mac example.`
			
			`We recommend using https://regex101.com/ for testing expressions.`

Match All Header Fields	toggles between granting access when any or all HTTP header fields match	• checkmark	
Consolation Prize HTML Element	targets an HTML element and allows restricted users to see that content; use the **HTML Wrap** macro and its **Hide** parameter to insert the consolation prize element		

* Removed in 2.0.

Info

Related

- Restrict Content Macro
- Macro Reference