

Restrict Content Macro Parameters and Key

Relates To

THEME PRESS

Restrict Content Macro Parameters and Key

Prompt

Restrict Content macro key and configuration options.

Key Title

Key

Key

restrict-content

Reference

Parameter	Description	Value(s)	Example(s)
Space Key(s)	grants access to space viewers; when the Any Space box is unchecked, users must have the View permission for all spaces	space key	- PRESS PINBOARDS - PRESS, PINBOARDS
Any Space	toggles between granting access to viewers of all spaces or any space	checkboxmark	
Page Title	grants access to users who can view the specified page	page title	- Theme Press Macros - PRESS:Theme Press Macros
Authenticated Users	defines how to handle access for authenticated users; inherit current macro restrictions, hide content, show content	- inherit - hide - show	
Anonymous Users	defines how to handle access for anonymous users; inherit current macro restrictions, hide content, show content	- inherit - hide - show	
Client Type	grants access to a specific type of computer client	- all - desktop - mobile	all
Allow Users	grants access to a list of users	usernames	charles_dickens,emily_dickinson
Allow Groups	grants access to a list of groups	user groups	confluence-users,theme-press-users
Exclude Users	restricts access from a list of users	usernames	charles_atlas,robbie_lee
Exclude Groups	restricts access from a list of groups	user groups	space-editors,guests
Display in Paragraph*	toggles between showing restricted content inline with other content or within its own paragraph	checkboxmark	

HTTP Header Fields	grants access to HTTP requests when the HTTP header field matches any of the specified name/value pairs	header-name=value	Plain matches: - City=Seattle - City=Seattle;City=Portland Regular expression matches[†]: - ipaddress=/128\. 128\. 200\. d+/ ipaddress=/128\. 128\. 200\. d+/ ipaddress=/128\. 128\. 210\. d+/ User-Agent=/. *Mac. */ [†]Entire value must match. Use . * or . + to match unknown characters, as in the Mac example. We recommend using https://regex101.com/ for testing expressions.
Match All Header Fields	toggles between granting access when any or all HTTP header fields match	checkmark	
Consolation Prize HTML Element	targets an HTML element and allows restricted users to see that content; use the HTML Wrap macro and its Hide parameter to insert the consolation prize element		

* Removed in 2.0.

Info

Related

- [Restrict Content Macro](#)
- [Macro Reference](#)